

ColorWorks C7500

Inkjet label printer

Label Printers

Industrial



Fast, full-color label printer for Just in Time Color™ printing.

Reliable performance — rugged design means minimal maintenance and a low overall cost of ownership; ideal for busy, on-demand environments

Powerful productivity — Just in Time Color printing for high-volume labeling applications

High-speed, on-demand, color printing — speed through multiple full-color labels with variable data up to 11.8" per second¹

Durable labels — BS-5609 certification means labels won't smudge, smear or fade²

Low cost of labeling — up to 50 percent lower printing cost than with laser and thermal transfer printers for high-durability color labels³

Seamless integration — built-in ESC/Label language means you can use the printer with your existing workflow, and even add color with simple programming extensions

Astounding image quality — powered by PrecisionCore™ inkjet technology from Epson; delivers precise barcodes and ultra sharp text

Highly efficient — high-yield ink cartridges mean fewer user interventions and less waste than most thermal transfer printers; easy to change, so there's less downtime

Printer

Print method: PrecisionCore TFP[®] with Nozzle Verification Technology

Ink type: Pigmented ink, 4 individual CMYK cartridges

Print resolution: 1200 x 600 dpi

Print speed: 300mm/s

Print width: 4.1" (104mm) max.

Media types: Roll-fed or fan fold, die cut; single layer or adhesive labels on liner; plain paper, fine paper, PET film, synthetic

Media Dimensions

Width: 2" – 4.25" (50 – 108mm) — roll feed

Thickness: 4.7 – 7.5mils (0.12 – 0.19mm)

Roll size O.D.: 8.0" (204mm) max.

Core diameter: 3" (76mm)

Media sensors: Gap, black mark

Die-cut label gap: Min. 0.12" (3.0mm)

Black mark size: Min. 1.1" x 0.2" (28mm x 5mm) (W x H)

General

Interfaces: USB 2.0 High-speed, Ethernet 10/100 BASE-T

Operating system: Microsoft[®] Windows[®] 8.1 (32-bit, 64-bit), Windows 8 (32-bit, 64-bit), Windows 7 SP1 (32-bit, 64-bit), Windows Vista[®] SP2 (32-bit, 64-bit), Windows XP SP3 (32-bit), Windows Server[®] 2012 R2, Windows Server 2012, Windows Server 2008 R2, Windows Server 2008 (32-bit, 64-bit), Windows Server 2003 R2 (32-bit)

General (continued)

Barcode font: UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded

Two-dimensional code printing: PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, DataMatrix, Aztec Code, MicroPDF417, Micro QR Code

Operating temperature

5 to 35 °C / 20 – 80% RH humidity

Storage temperature

-20 to 60 °C / 5 – 85% RH humidity

Overall dimensions

15.4" x 23.5" x 15.5" (W x D x H) — Printer

Weight

Approximately 37.0 kg (81.57 lb) — Printer (without ink)

Power consumption

50 – 60 W Printing (average printing)

4.1 – 4.4 W Standby

0.2 – 0.5 W Power Off state

Rated voltage

AC 100 – 240 VAC

Rated frequency

50 – 60 Hz

Acoustic noise approx.

55 dBA

EMI

FCC / ICES-003 Class B

Safety standards

UL60950-1/CSA C22.2 No.60950-1

Warranty

One year depot repair

What's in the Box

ColorWorks C7500 printer, AC power cord, full capacity ink cartridges, sample label roll, instruction sheet, CD with utilities and manuals

Ordering Information

TM-C7500-011 Color Label Printer	C31CD84011
TU-RC7508-471 Take Up Unit Option	C32C815471
SJIC26P (C) Cyan Ink	C33S020615
SJIC26P (B) Black Ink	C33S020614
SJIC26P (M) Magenta Ink	C33S020616
SJIC26P (Y) Yellow Ink	C33S020617
SJMB7500 Maintenance Box	C33S020596

Simple
Solutions...



... to Complicated
Problems