

# L801 Industrial Color Label Printer

## Incredible Print Quality with Industry-Leading Low Cost of Ownership

The easy-to-use L801 Industrial Color Label Printer is powered by Memjet “waterfall” technology. Built with a stationary printhead for ultimate speed, and a 1.25 liter ink capacity for large print runs, the L801 saves you both time and money.

The L801 Memjet label printer is an industrial web-fed inkjet solution, ideal for short- to medium-range print runs for retail, inventory, and product identification applications.

### Key Features

- ✓ Print speed of up to 60 feet/minute
- ✓ Industry-leading ink cost per label
- ✓ Variable data capability
- ✓ Compatible with a wide range of label stock
- ✓ Exceptionally crisp images and text



### Memjet-powered stationary printhead

Enables ultimate speed, quality, and reliability

### Professional image quality & resolution

Exceptionally crisp images and text with vibrant color and rich blacks

### Wide range of media compatibility

Choose the label stock that creates the best look and feel for your brand

### Easy access

For simplified maintenance and servicing

### Large ink capacity (CMYKK)

Supports large runs and offers industry-leading ink cost



*Simple  
Solutions...*

# TEXPAK INC.

*... to Complicated  
Problems*

www.texpak.com

130 New Hyde Park Road, Franklin Square, New York 11010

info@texpak.com

800-645-3416

# L801 Specifications

## Printer:

<b>Print method:</b>	Memjet Waterfall Printhead Technology® 11 Integrated Circuit (IC) Chips – 70,400 nozzles
<b>Ink type:</b>	Dye
<b>Print resolution:</b>	1600 x 1600 dpi or 1600 x 800 dpi
<b>Print speed:</b>	6 inches (152 mm) per second or 12 inches (305 mm) per second
<b>Print width:</b>	8.5 inches (216 mm)
<b>Media types:</b>	compatible with a wide range of paper, polyester, polypropylene, and vinyl label stocks

## Media:

<b>Media width:</b>	2"–8.5" (50.8 mm–216 mm)
<b>Thickness:</b>	Minimum 0.005" (0.13 mm) Maximum 0.01" (0.3 mm, including liner)
<b>Core diameter:</b>	Requires 3" (76.2 mm) cardboard core
<b>Media sensors:</b>	Gap, continuous, black mark
<b>Die-cut label gap:</b>	Minimum 0.125" (3.0 mm) Maximum 0.3" (8.0 mm)
<b>Black mark size:</b>	(3 mm wide, 25.4 mm long on left)

## General:

<b>Interfaces:</b>	USB, TCP/IP (Manual IP configuration or DHCP), GPIO available for external device control
<b>Operating system:</b>	Windows 7, 8, and 10 (32 and 64 bit)
<b>Barcode font:</b>	1D Barcode at least Grade B (Code39) with 10mils bar width
<b>Two-dimensional code</b>	2D Barcode at least Grade B (PDF417) with 10mils cell size
<b>Operating temperature:</b>	15°–35° C (59°–95°F) at RH 20–80%
<b>Storage temperature:</b>	-5°–50° C (23°–113°F) at RH up to 85%, non-condensing at 65°
<b>Overall dimensions:</b>	18.9" (480mm) W, 19" (485mm) D, 21.1" (535mm) H
<b>Weight:</b>	83 lbs. (37.6kg)
<b>Rated voltage:</b>	AC 110V – 220V
<b>Rated frequency:</b>	50 – 60Hz
<b>Warranty:</b>	One year



**Label Printing Solutions for Every Level of Production**

*Simple  
Solutions...*

[www.texpak.com](http://www.texpak.com)

130 New Hyde Park Road, Franklin Square, New York 11010

**TEXPAK** INC.

*... to Complicated  
Problems*

[info@texpak.com](mailto:info@texpak.com)

800-645-3416